

DATASHEET

EMERGENCY RELIEF MANHOLE COVER FOR BULK STORAGE TANKS

CNC 121 / 122 Series Emergency Relief Manhole Cover

121



APPLICATION


Motherwell Tank Protection (MTP) CNC121 and CNC122 non-sparking emergency relief manhole covers permit access to low pressure storage tanks and provides emergency venting capacity in the event of fire.

CNC121/122 series valves are used extensively on **bulk storage tanks**, including floating roof tanks, they are manufactured by MTP in our UK manufacturing plant to exacting quality standards and backed by over 40 years experience. Sizes range from 10" (250mm) to 24" (600mm).

BENEFITS

- Hinged pallet can be manually lifted allowing access to the tank for cleaning and inspection with no gasket replacement or unbolting necessary.
- Range of sizes and materials to suit a wide range of applications
- Wide range of pressure settings to provide maximum tank protection whilst ensuring minimum gas loss
- Low cost maintenance.
- FREE valve sizing service assists optimum valve performance/cost specification.
- ATEX approved to directive 94/9/EC

PRINCIPLE OF OPERATION




Emergency relief manways are fitted to storage tanks to allow emergency flow due to the excessive venting requirement from a fire burning around a storage tank. This eliminates a costly tank rupture, providing emergency venting from abnormal internal pressure beyond the capability of the pressure relief vent. In the event of a fire the pallet will lift at a predetermined pressure, thus supplying a large venting area.


The design of the this model employs a PTFE insert affording a tight seal below set pressure between the pallet and the corrosion resistant seat.

THE CNC122 model is fitted with an additional spring-loaded vacuum valve that will open under negative pressure to protect the tank from any vacuum condition damage that may occur.



Normal Settings






High Settings

Low Settings

SPECIFICATION



GENERAL DESCRIPTION MTP Emergency Relief Manhole Cover

APPLICATION Bulk Storage Tanks, Low pressure gas pipeline systems, Digesters, Gas Holders

PHYSICAL Model 121 or 122

> Sizes 10" 12" 18" 20" 24"

Process Connection 1. API650 (20" and 24")

2. ANSI 150#

3. Special (Flange drilling as requested)

Materials 1. Aluminium

2. Cast Iron

3. Carbon Steel 4. Stainless Steel

Special (Available upon request)

Diaphragm & Insert 1. PTFE

1. Lead Plate (Standard) Weight

2. Stainless Plate (Special)

3"wg (7.5mbar) - 36.2"wg (90mbar) 3.46"wg (9mbar) - 10"wg (25mbar) Pressure Settings **PROCESS**

Vacuum Settings (CNC122)

ORDERING CODE MODEL-SIZE-MATERIAL-DIAPHRAGM & INSERT + P/V Settings

> (121 series, 12" API650 connection, carbon steel body, PTFE diaphragm e.g. 121-12-1311

and insert, lead weights)

VALVE SIZING - FREE SERVICE Computerised valve sizing to API 2000, contact us on the numbers below.

AFTER SALES SUPPORT MTP provide comprehensive spares support, a free valve inspection service and term preventative maintenance schemes using product-trained technicians to service MTP and other

brands of valves and fittings.

Motherwell Tank Protection

St Michaels Road Lea Green Ind Est St Helens Merseyside England WA9 4WZ

Tel : + 44 1744 815211 Fax: +44 1744 814497

sales@motherwelltankprotection.co.uk www.motherwelltankprotection.co.uk









