

DATASHEET

FREE VENT FOR BULK STORAGE TANKS

CNC 240 Free Vent

240



APPLICATION

BENEFITS

PRINCIPLE OF OPERATION

PHYSICAL

Motherwell Tank Protection (MTP) CNC 240 free vent permits atmospheres and vapors to flow freely in tanks or vent riser pipes.

- Range of sizes and materials to suit a wide range of applications.
- FREE SIZE SELECTION carried out by MTP, if required, to ensure suitability for venting requirements.
- Customised designs available to meet customer's specifications.
- Quick and easy installation.
- ATEX approved to directive 94/9/EC

Large streamlined mushroom type weather hood to permit maximum flow. The vent exit opening is fitted with a 304 stainless steel wire mesh screen to prevent the ingress of foreign matter.

Model

240

Sizes

2", 3", 4", 6", 8", 10", 12"

Process Connection

1. ANSI 150# (Standard)

2. PN10 / PN16

3. Special (Flange drilling as required)

Materials

1. Aluminium

Cast Iron

3. Carbon Steel

Stainless Steel

MODEL-SIZE-PROCESS CONNECTION-MATERIAL-INSERT

e.g. 240-02-14 (240 series, 2" ANSI 150# connection, stainless steel body)

AFTER SALES SUPPORT

ORDERING CODE

MTP provide comprehensive spares support, and term preventative maintenance schemes using product-trained technicians to service MTP and other brands of valves and fittings.

Motherwell Tank Protection

St Michaels Road Lea Green Ind Est St Helens Merseyside England WA9 4WZ

Tel : + 44 1744 815211 Fax: +44 1744 814497

sales@motherwelltankprotection.co.uk www.motherwelltankprotection.co.uk









